



See online
technical sheet

/ EY322NFC

Earthing and short-circuiting device, with spring line clamps



/ Standards

- CEI 61230

/ Use

MT330NFC gripper version with locking latch.




Pre-arming of the gripper directly on the plate, with locking of the gripper on the plate.

Automatic closing and release of the clamp from the tray when placed on the conductor, by unlocking the latch.

/ Advantages

- Automatic spring clamp, no manual tightening required
- High clamping capacity
- Fast and easy to use

/ Areas of activity

-  Electrical distribution
-  Civil security
-  Transport

/ Technical specifications

- Product kind : Dispositif
- Clamp material : Aluminium
- Clamp tightening (mm) : Ø3 à 32mm
- Conductor type : Round
- Operating voltage (V) : HTA (1 000 V to 50 000 V)
- Field of use (environment) :
- In line (aerial) : Isolated
- Way of access : From the floor
- From the floor : Columns
- Cable material : Copper
- Phase cable number : 2



/ Table legend

Other cross-sections and cable lengths on request.

Product reference	Phase(s) cable length (m)	Short-circuit intensity kA/0.5s	Short-circuit intensity kA/1s	Cross-section (mm ²)	Floor cable length (m)	Phase(s) cable cross-section (mm ²)	Weight (kg)
EY3222NFC6	2,75	9,5	6,5	16	25	25	23,0
EY3221NFC	2,25	13	8	16	16	35	23,5
EY3222NFC	2,75	13	8	16	16	35	24,0
EY3222NFC13	2,75	18,5	13	25	16	50	25,0
EY3222NFC18	2,75	-	-	70	14	70	26,0