

PAB e-Two 30

ATPV 36 cal/cm²
ABS/PCA



No responsibility assumed for any printing errors. / Due to the continuous development and improvement of our products, including those shown in this catalogue, there may be certain technical differences between the indicated and the actual characteristics of the currently available products. This applies to technological, technical and design features. / February 2024

PAB e-Two 30 double shell with chin protector

Modern designed helmet that offers the best protection, great comfort and possibility of different applications in areas of energy, oil & gas and industry.

PERFORMANCE

- Low-temperature classification -30°C
- Resistance to lateral deformation (LD)
- Resistance to molten metal splashes (MM)
- Electrically insulating helmet for use on low voltage installations (up to 1000 V a.c. or 1500 V d.c.) with additional electric arc protection

SAFETY

- Electric arc protection (Class 2 + ATPV 36 cal/cm²)
- Protection against low voltage electric current (Class 0)
- Optional : Lamp attachment
- Chinstrap anchorage resistance

COMFORT

- Integrated size regulation system (52 63 cm)
- Lightweight
- 4-point chinstrap
- Retractable PC visor with optimal distance from the wearer's face (allows to wear glasses,)
- Lamp attachment optional

WEIGHT

■ 1020 g ± 20 g

HIGH TECH MATERIALS

Impact and heat resistant thermoplastic (Double shell system)





COMPLIANCE WITH STANDARDS:

EN 397:2012+A1 (2012) | EN 50365:2002 (class 0) | EN 166:2001 | GS ET 29 (class II) | EN 170:2001 | ASTM F 2178:2012 ATPV 36 cal/cm²

COLOR SCALE

PAB WHITE











Your PAB Akrapović partner:

PAB Akrapović

Most 26, HR-52420 Buzet, Croatia P +385 52 662 662 | F +385 52 662 254 info@pab.hr | www.pab.hr