



**PAB** Akrapović

# PAB e-Two 40

ATPV 44 cal/cm<sup>2</sup>  
ABS/PCA



No responsibility assumed for any printing errors. / Due to the continuous development and improvement of our products, including those shown in this catalogue, there may be certain technical differences between the indicated and the actual characteristics of the currently available products. This applies to technological, technical and design features. / February 2024

# PAB e-Two 40

## double shell with chin protector

Modern designed helmet that offers the best protection, great comfort and possibility of different applications in areas of energy, oil & gas and industry.

### PERFORMANCE

- Low-temperature classification -30°C
- Resistance to lateral deformation (LD)
- Resistance to molten metal splashes (MM)
- Electrically insulating helmet for use on low voltage installations (up to 1000 V a.c. or 1500 V d.c.) with additional electric arc protection

### SAFETY

- Electric arc protection (Class 2 + ATPV 44 cal/cm<sup>2</sup>)
- Protection against low voltage electric current (Class 0)
- Optional : Lamp attachment
- Chinstrap anchorage resistance

### COMFORT

- Integrated size regulation system (52 - 63 cm)
- Lightweight
- 4-point chinstrap
- Retractable PC visor with optimal distance from the wearer's face (allows to wear glasses,)
- Lamp attachment - optional

### WEIGHT

- 1020 g ± 20 g

### HIGH TECH MATERIALS

- Impact and heat resistant thermoplastic (Double shell system)



### COMPLIANCE WITH STANDARDS:

EN 397:2012+A1 (2012) | EN 50365:2002 (class 0) | EN 166:2001 | GS ET 29 (class II) | EN 170:2001 | ASTM F 2178:2012 ATPV 44 cal/cm<sup>2</sup>

### COLOR SCALE



Your PAB Akrapović partner:

**PAB Akrapović**

Most 26, HR-52420 Buzet, Croatia  
P +385 52 662 662 | F +385 52 662 254  
info@pab.hr | www.pab.hr